



MDF 400 SERIES DRINKING FOUNTAIN SPECIFICATIONS

WATER QUALITY (LEAD FREE)

Fountain meets NSF-61 requirements and has a UL approved label with a UL tracking number.

PEDESTAL

One piece weld construction with MDF standard $\frac{3}{16}$ " wall thickness **or optional** 304 schedule 10 stainless steel.

RECEPTOR BOWL

18 gauge electro-polished stainless steel bowl. Bowl overlaps pedestal by $\frac{9}{16}$ ". Prevents build-up of residue in visual drinking area. Optional SS Bowl Strainer recommended for areas with sand.

BUBBLER HEAD

Heavy-duty, stainless steel anti-squirt head mounted with lock nut and washer to prevent tampering. Designed to deliver a constant stream trajectory. Natural shield to prevent contamination.

PUSH BAR

304 stainless steel with $1\frac{1}{4}$ " x 2" stainless steel housing. Mushroom style push bar overlaps and prevents sand and other objects from sticking push bar in the ON position.

CONTROL VALVE

Non-cartridge stainless steel O-Ring valve delivers non-spurt, adjustable steady stream of water. Washerless.

WATER SUPPLY (LEAD FREE)

Maintenance-free reinforced nylobraid tubing and fittings, NSF-61 certified. This tubing is not plastic. It is supplied with a $\frac{1}{2}$ " MIP threaded inlet with a stainless steel strainer. Union fittings at every connection. Supply line stops above grade.

FINISH

Oven-baked powder coat. Color choices: green, blue, brown, black, red, yellow, orange, white and chrome. Textured color choices: emerald, sapphire, pyrite, text-black, burgundy, gold vein, copper and sandstone. Stainless Steel fountains are powder coated for added protection and all colors listed are available.

WASTE

$1\frac{1}{2}$ " schedule 40 PVC pipe. Waste line stops above grade.

ACCESS

Working parts accessible through bowl of fountain for easy service.

INSTALLATION

Optional installations are **DIRECT BURY** or **SURFACE MOUNT**. Direct Bury is designed to be buried a depth of 14" in the ground with concrete poured around it. Surface Mount is designed to be anchored on top of an existing surface (concrete, etc.) with anchor bolts through a mounting plate that is welded to the fountain. Surface Mount fountains provide an access door with vandal-resistant stainless steel screws. Surface Mount Carrier recommended for all surface mount installations. Access door standard on all pedestal fountains. Flush Supply line before installing.

WINTERIZATION

Shut off water and drain down.

WARRANTY

One year warranty. Labor not included.

SHIPPING WT.

Model 400	125 lbs.	Model 450*	45 lbs.
Model 410*	150 lbs.	Model 493*	150 lbs.
Model 440*	150 lbs.	<i>* Meets ADA regulations</i>	

Note: When ordering, please specify installation by DB or SM, and stainless steel by SS. Always note your color choice and options where applicable. (Options are added at an additional cost to the customer.) Example: Specify 410 DBSS to order 410 Direct Bury Stainless Steel. Please call MDF to assist you with ordering, quoting and shipping.

MOST DEPENDABLE FOUNTAINS, INC.
 (800) 552-6331 • (901) 867-0039 • Fax (901) 867-4008
 5705 COMMANDER DR. • ARLINGTON, TN 38002-0587
www.mostdependable.com

