



# MDF 40018 CHILLED SERIES DRINKING FOUNTAIN SPECIFICATIONS

## WATER QUALITY (LEAD FREE)

Fountain meets NSF-61 requirements and has a UL approved label with a UL tracking number.

## PEDESTAL

One piece weld construction with MDF standard  $\frac{3}{16}$ " wall thickness **or optional** 304 schedule 10 stainless steel.

## RECEPTOR BOWL

18 gauge electro-polished stainless steel bowl. Bowl overlaps pedestal by  $\frac{9}{16}$ ". Prevents build-up of residue in visual drinking area. Optional SS Bowl Strainer recommended for areas with sand.

## BUBBLER HEAD

Heavy-duty, stainless steel anti-squirt head mounted with lock nut and washer to prevent tampering. Designed to deliver a constant stream trajectory. Natural shield to prevent contamination.

## PUSH BAR

304 stainless steel with  $1\frac{1}{4}$ " x 2" stainless steel housing. Mushroom style push bar overlaps and prevents sand and other objects from sticking push bar in the ON position.

## CONTROL VALVE

Non-cartridge stainless steel O-Ring valve delivers non-spurt, adjustable steady stream of water. Washerless.

## WATER SUPPLY (LEAD FREE)

Maintenance-free reinforced nylobraid tubing and fittings, NSF-61 certified. This tubing is not plastic. It is supplied with a  $\frac{1}{2}$ " MIP threaded inlet with a stainless steel strainer. Union fittings at every connection. Supply line stops above grade.

## FINISH

Oven-baked powder coat. Color choices: green, blue, brown, black, red, yellow, orange, white and chrome. Textured color choices: emerald, sapphire, pyrite, text-black, burgundy, gold vein, copper and sandstone. Stainless Steel fountains are powder coated for added protection and all colors listed are available.

## WASTE

$1\frac{1}{2}$ " schedule 40 PVC pipe. Waste line stops above grade.

## ACCESS

Working parts accessible through bowl of fountain for easy service.

## INSTALLATION

**SURFACE MOUNT** only. Surface Mount is designed to be anchored on top of an existing surface (concrete, etc.) with anchor bolts through a mounting plate that is welded to the fountain. Surface Mount fountains provide an access door with vandal-resistant stainless steel screws. Surface Mount Carrier recommended for all surface mount installations. Access door standard on all pedestal fountains. Flush Supply line before installing.

## WINTERIZATION

Shut off water and drain down. Remove chiller if applicable.

## WARRANTY

One year warranty. Labor not included.

## CHILLER

Chilling capacity 8 gallons per hour. NO Lead design. 115 VAC.

## SHIPPING WT.

Model 40018.....	240 lbs.	Model 41018*.....	240 lbs.
Model 44018*.....	295 lbs.	Model 49318*.....	325 lbs.

\* Meets ADA regulations

**Note:** When ordering, please specify stainless steel by SS. Always note your color choice and options where applicable. (Options are added at an additional cost to the customer.) Example: Specify 41018 SMSS to order 41018 Surface Mount Stainless Steel. Please call MDF to assist you with ordering, quoting and shipping.

**MOST DEPENDABLE FOUNTAINS, INC.**  
 (800) 552-6331 • (901) 867-0039 • Fax (901) 867-4008  
 5705 COMMANDER DR. • ARLINGTON, TN 38002-0587  
 www.mostdependable.com

