



# AGGREGATE SERIES DRINKING FOUNTAIN SPECIFICATIONS

## WATER QUALITY (LEAD FREE)

Fountain meets NSF-61 requirements and has a UL approved label with a UL tracking number.

## PEDESTAL

Aggregate stone.

## RECEPTOR BOWL

18 gauge electro-polished stainless steel bowl. Optional SS Bowl Strainer recommended for areas with sand.

## BUBBLER HEAD

Heavy-duty, stainless steel anti-squirt head mounted with lock nut and washer to prevent tampering. Designed to deliver a constant stream trajectory. Natural shield to prevent contamination.

## PUSH BAR

304 stainless steel with 1 1/4" x 2" stainless steel housing. Mushroom style push bar overlaps and prevents sand and other objects from sticking push bar in the ON position.

## CONTROL VALVE

Non-cartridge stainless steel O-Ring valve delivers non-spurt, adjustable steady stream of water. Washerless.

## WATER SUPPLY (LEAD FREE)

Maintenance-free reinforced nylobraid tubing and fittings, NSF-61 certified. This tubing is not plastic. It is supplied with a 1/2" MIP threaded inlet with a stainless steel strainer. Union fittings at every connection. Supply line stops above grade.

## WASTE

1 1/2" schedule 40 PVC pipe. Waste line stops above grade.

## ACCESS

Working parts accessible through bowl of fountain for easy service. Access door on main pedestal.

## INSTALLATION

**SURFACE MOUNT** only. Surface Mount is designed to be anchored on top of an existing surface (concrete, etc.) with anchor bolts through a mounting plate that is welded to the fountain. Surface Mount fountains provide an access door with vandal-resistant stainless steel screws. Surface Mount Carrier recommended for all surface mount installations. Access door standard on all pedestal fountains. Flush Supply line before installing.

## WINTERIZATION

Shut off water and drain down.

## WARRANTY

One year warranty. Labor not included.

## SHIPPING WT.

Model 3000 SM .....	385 lbs.	Model 3900 SM CU* .....	490 lbs.
Model 3300 SM .....	447 lbs.	Model 3600 CU .....	390 lbs.
Model 3700 SM* .....	425 lbs.	<i>* Meets ADA regulations</i>	
Model 3800 SM* .....	500 lbs.		

**Note:** When ordering an aggregate drinking fountain, please specify the applicable options at time of order. (Options are added at an additional cost to the customer.) Example: Specify Model 3700 SM with Kit UAVB to order a 3700 Surface Mount with an optional unattached valve box. Please call MDF to assist you with ordering, quoting and shipping.

**MOST DEPENDABLE FOUNTAINS, INC.**  
 (800) 552-6331 • (901) 867-0039 • Fax (901) 867-4008  
 5705 COMMANDER DR. • ARLINGTON, TN 38002-0587  
[www.mostdependable.com](http://www.mostdependable.com)

