



HISTORICAL DRINKING FOUNTAIN SPECIFICATIONS

WATER QUALITY (LEAD FREE)

Fountain meets NSF-61 requirements and has a UL approved label with a UL tracking number.

PEDESTAL

One piece weld construction of ANSI 380 aluminum alloy. (Note: This alloy is better than 384 in share strength & tensile strength.)

RECEPTOR BOWL

18 gauge electro-polished stainless steel bowl. Bowl overlaps pedestal by ⁹/₁₆". Prevents build-up of residue in visual drinking area. Optional SS Bowl Strainer recommended for areas with sand.

BUBBLER HEAD

Heavy-duty, stainless steel head mounted with lock nut and washer to prevent tampering. Designed to deliver a constant stream trajectory. Natural shield to prevent contamination.

PUSH BAR

304 stainless steel with 1¹/₄" x 2" stainless steel housing. Mushroom style push bar overlaps and prevents sand and other objects from sticking push bar in the ON position.

CONTROL VALVE

Requires less than 5 lbs to operate. Non-cartridge O-ring valve delivers steady stream of water through flow regulator. This valve design is to operate and function at 30 to 80 PSI. Ideal operating pressure is 60 PSI.

WATER SUPPLY (LEAD FREE)

Maintenance-free reinforced nylobraid tubing and fittings, NSF-61 certified. **This tubing is not plastic.** It is supplied with a ¹/₂" MIP threaded inlet with a stainless steel strainer. Union fittings at every connection. Supply line stops above grade.

FINISH

Oven-baked powder coat. Textured color choices: emerald, sapphire, pyrite, text-black, burgundy, gold vein, copper and sandstone.

WASTE

1¹/₂" schedule 40 PVC pipe. Waste line stops above grade.

ACCESS

Working parts accessible through bowl of fountain for easy service.

INSTALLATION

SURFACE MOUNT installation. Surface Mount is designed to be anchored on top of an existing surface (concrete, etc.) with anchor bolts through a mounting plate that is welded to the fountain. Surface Mount fountains provide an access door with vandal-resistant stainless steel screws. Surface Mount Carrier recommended for all surface mount installations. Access door standard on all pedestal fountains.

WINTERIZATION

Shut off water and drain down.

WARRANTY

One year warranty. Labor not included.

SHIPPING WT.

Model 2002* 125 lbs. * *Meets ADA regulations*
Model 2008* 150 lbs.

Note: When ordering the 2002 SM, please specify the applicable options at time of order. Always note your color choice and options where applicable. (Options are added at an additional cost to the customer.) Example: Specify 2002 SM in emerald to order 2002 Surface Mount powder coated in textured emerald. Please call MDF to assist you with ordering, quoting and shipping.

MOST DEPENDABLE FOUNTAINS, INC.
(800) 552-6331 • (901) 867-0039 • Fax (901) 867-4008
5705 COMMANDER DR. • ARLINGTON, TN 38002-0587
www.mostdependable.com

