

## MODELS 24 AND 36 HYDRANTS SPECIFICATIONS

**PEDESTAL**

One piece weld construction with MDF standard  $\frac{3}{16}$ " wall thickness **or optional** 304 schedule 10 stainless steel.

**FAUCET**

Supplied with  $\frac{3}{4}$ " anti-siphon vacuum breaker, frost resistant sill cock with removeable handle.

**HOSE BIBB COVER**

Optional locking hose bibb cover recommended.

**INSTALLATION**

10" BURY in ground. Attached valve box with bolted Cover included, or SURFACE MOUNT available.

**WINTERIZATION**

Shut off water and drain down.

**SUPPLY LINE**

Maintenance free reinforced nylobraid inlet with strainer.

**FINISH**

Oven-baked powder coat. Color choices: green, blue, brown, black, red, yellow, orange, white and chrome. Textured color choices: emerald, sapphire, pyrite, text-black, burgundy, gold vein, copper and sandstone. Stainless Steel Hydrants are powder coated for added protection and all colors listed are available.


**WARRANTY**

One year warranty. Labor not included.

**SHIPPING WT.**

88 lbs.

### OPTIONS



Carrier

**MOST DEPENDABLE FOUNTAINS, INC.**  
(800) 552-6331 • (901) 867-0039 • Fax (901) 867-4008  
5705 COMMANDER DR. • ARLINGTON, TN 38002-0587  
[www.mostdependable.com](http://www.mostdependable.com)