

MDF JUG FILLER SPECIFICATIONS


PEDESTAL JUG FILLER

PEDESTAL	One piece weld construction with MDF standard $\frac{3}{16}$ " wall thickness or optional 304 schedule 10 stainless steel.
PUSH BAR	304 stainless steel with $1\frac{1}{4}$ " x 2" stainless steel housing. Mushroom style push bar overlaps and prevents sand and other objects from sticking push bar in the ON position.
VALVE	Quick opening self closing balanced valve of heavy brass construction, precision machined for positive seating.
INSTALLATION	10" bury in ground. Attached valve box with bolted cover included or surfact mount available.
WINTERIZATION	Shut off water and drain down.
SUPPLY LINE	Maintenance-free reinforced nylobraid tubing, supplied with a $\frac{3}{8}$ " MIP threaded inlet with strainer. Supply line stops above grade.
FINISH	Oven-baked powder coat. Color choices: green, blue, brown, black, red, yellow, orange, white and chrome. Textured color choices: emerald, sapphire, pyrite, text-black, burgundy, gold vein, copper and sandstone. Stainless Steel Pedestal Jug Fillers are powder coated for added protection and all colors listed are available.
SHIPPING WT.	65 lbs.

WALL MOUNT JUG FILLER

PEDESTAL	10 gauge steel.
PUSH BAR	304 stainless steel with $1\frac{1}{4}$ " x 2" stainless steel housing. Mushroom style push bar overlaps and prevents sand and other objects from sticking push bar in the ON position.
VALVE	Quick opening self closing balanced valve, precision machined for positive seating.
INSTALLATION	Wall mounted (see drawing).
WINTERIZATION	Shut off water and drain down.
SUPPLY LINE	Maintenance-free reinforced nylobraid tubing, supplied with a $\frac{3}{8}$ " MIP threaded inlet with strainer.
FINISH	Stainless Steel.
SHIPPING WT.	65 lbs.

OPTIONS



Carrier

MOST DEPENDABLE FOUNTAINS, INC.
(800) 552-6331 • (901) 867-0039 • Fax (901) 867-4008
5705 COMMANDER DR. • ARLINGTON, TN 38002-0587
www.mostdependable.com