



MISTER SPECIFICATIONS

MODEL 535

PEDESTAL

One piece weld construction with MDF standard $\frac{3}{16}$ " wall thickness **or optional** 304 schedule 10 stainless steel.

VALVE

One metered valve with an approximate run time of two minutes.

HEADS

Eight misting heads. Manufactured with eight 1 GPH misting heads. One metered valve with an approximate run time of two minutes.

INSTALLATION

SURFACE MOUNT (SM) Mistors are designed to be anchored to a concrete slab, by means of quick bolts or concrete shields. Surface Carrier is recommended for all surface mount installations. There have been instances where the surfact mount Mistors have been anchored to boardwalks or wooden decks.

DIRECT BURY (DB) Mistors are designed to be buried 14" in the ground with a concrete slab poured around it.

WINTERIZATION

Shut off water and drain down.

SUPPLY LINE

Maintenance-free reinforced $\frac{3}{8}$ " nylobraid tubing, provided with a water strainer. Customer connection is a $\frac{1}{2}$ " MIP threaded inlet. Supply line stops above grade.

FINISH

Oven-baked powder coat. Color choices: green, blue, brown, black, red, yellow, orange, white and chrome. Textured color choices: emerald, sapphire, pyrite, text-black, burgundy, gold vein, copper and sandstone. Stainless Steel Showers have a powder coat finish for added protection and all colors listed are available.

SHIPPING WT.

130 lbs.

MODEL 530 SM

PEDESTAL

One piece weld construction with MDF standard $\frac{3}{16}$ " wall thickness **or optional** 304 schedule 10 stainless steel.

VALVE

One metered valve with an approximate run time of two minutes.

HEADS

Ten misting heads. Manufactured with twelve 1 GPH misting heads. One metered valve with an approximate run time of two minutes.

INSTALLATION

Model 530 Mister is designed to be anchored to a concrete slab, by means of our 4 template that is set in concrete. Stainless Steel Surface Carrier is included.

WINTERIZATION

Shut off water and drain down.

SUPPLY LINE

Maintenance-free nylobraid tubing. Customer connection is a $\frac{1}{2}$ " MIP threaded inlet. Supply line stops above grade.

FINISH

Oven-baked powder coat. Color choices: green, blue, brown, black, red, yellow, orange, white and chrome. Textured color choices: emerald, sapphire, pyrite, text-black, burgundy, gold vein, copper and sandstone. Stainless Steel Showers have a powder coat finish for added protection and all colors listed are available.

SHIPPING WT.

175 lbs.

Note: When ordering, please specify installation by DB or SM, and stainless steel by SS. Always note your color choice and options where applicable. (Options are added at an additional cost to the customer.) Example: Specify 535 SMSS to order Model 535 Surface Mount Stainless Steel. Please call MDF to assist you with ordering, quoting and shipping.

MOST DEPENDABLE FOUNTAINS, INC.
(800) 552-6331 • (901) 867-0039 • Fax (901) 867-4008
5705 COMMANDER DR. • ARLINGTON, TN 38002-0587
www.mostdependable.com