



MDF 500 SERIES FOOT & SHOWER TOWER SPECIFICATIONS

PEDESTAL

One piece weld construction with MDF standard $\frac{3}{16}$ " wall thickness **or optional** 304 schedule 10 stainless steel.

PUSH BAR

304 stainless steel with $1\frac{1}{4}$ " x 2" stainless steel housing. Mushroom style push bar overlaps and prevents sand and other objects from sticking push bar in the ON position.

SPRAY HEADS

One Shower and one Foot Spray Head.

VALVE

Quick opening self closing valve.

INSTALLATION

DIRECT BURY (DB) Showers are designed to be buried 14" in the ground with a concrete slab poured around it.

SURFACE MOUNT (SM) Showers are designed to be anchored to a concrete slab, by means of quick bolts or concrete shields. There have been instances where the surfact mount showers have been anchored to boardwalks or wooden decks.

WINTERIZATION

Shut off water and drain down.

SUPPLY LINE

Maintenance-free reinforced $\frac{3}{8}$ " nylobraid tubing and $\frac{1}{2}$ " IPS with inlet water strainer. Supply line stops above grade.

FINISH

Oven-baked powder coat. Color choices: green, blue, brown, black, red, yellow, orange, white and chrome. Textured color choices: emerald, sapphire, pyrite, text-black, burgundy, gold vein, copper and sandstone. Stainless Steel fountains are powder coated for added protection and all colors listed are available.

SHIPPING WT.

Model 500	130 lbs.	Model 575	130 lbs.
Model 525	90 lbs.	Model 580	200 lbs.
Model 550	170 lbs.	Model 590	150 lbs.
Model 565	175 lbs.		

Above specifications apply with these notes:

Model 500 – One shower and one foot spray.

Model 525 – Foot Tower - one head only.

Model 550 – See Foot & Shower Tower Specifications and 400 Series Drinking Fountain Specifications.

Model 565 – Accessible Shower with one metered head at 72" and one metered head at 49" on the same side, two grab bars and one foot wash with quick closing valve.

Model 575 – Dual (back-to-back) shower and foot spray heads.

Model 580 – See Foot & Shower Tower Specifications and 810 Series Drinking Fountain Specifications.

Model 590 – Spray Heads: Four Shower and one Foot spray head.

Model 500-8 – Denotes custom, call for information.

Note: When ordering, please specify installation by DB or SM, and stainless steel by SS. Always note your color choice and options where applicable. (Options are added at an additional cost to the customer.) Example: Specify 500 DBSS to order 500 Direct Bury Stainless Steel. Please call MDF to assist you with ordering, quoting and shipping.

MOST DEPENDABLE FOUNTAINS, INC.
 (800) 552-6331 • (901) 867-0039 • Fax (901) 867-4008
 5705 COMMANDER DR. • ARLINGTON, TN 38002-0587
www.mostdependable.com

