



MDF MODEL 350 PET DRINKING FOUNTAIN SPECIFICATIONS

WATER QUALITY

Fountain meets NSF-61 requirements and has a UL approved label with a UL tracking number.

PEDESTAL

One piece weld construction with MDF standard $\frac{3}{16}$ " wall thickness **or optional** 304 schedule 10 stainless steel.

RECEPTOR BOWL

18 gauge electro-polished stainless steel bowl. Bowl overlaps pedestal by $\frac{9}{16}$ ". Prevents build-up of residue in visual drinking area. Optional SS Bowl Strainer recommended for areas with sand.

BUBBLER HEAD

Heavy-duty, stainless steel anti-squirt head mounted with lock nut and washer to prevent tampering.

PUSH BAR

Foot Activated 304 stainless steel with $1\frac{1}{4}$ " x 2" stainless steel housing. Low clearance between push bar and housing prevents objects from sticking push bar in the ON position.

CONTROL VALVE

Non-cartridge stainless steel O-Ring valve delivers non-spurt, adjustable steady stream of water. Washerless.

WATER SUPPLY (LEAD FREE)

Maintenance-free reinforced nylobraid tubing and fittings, NSF-61 certified. This tubing is not plastic. It is supplied with a $\frac{1}{2}$ " MIP threaded inlet with a stainless steel strainer. Union fittings at every connection. Supply line stops above grade.

FINISH

Oven-baked powder coat. Color choices: green, blue, brown, black, red, yellow, orange, white and chrome. Textured color choices: emerald, sapphire, pyrite, text-black, burgundy, gold vein, copper and sandstone. Stainless Steel fountains are powder coated for added protection and all colors listed are available.

WASTE

$1\frac{1}{2}$ " schedule 40 PVC pipe. Waste line stops above grade.

ACCESS

Working parts accessible through bowl of fountain for easy service.

INSTALLATION

Surface Mount is designed to be anchored on top of an existing surface (concrete, etc.) with anchor bolts through a mounting plate that is welded to the fountain. Surface Mount fountains provide an access door with vandal-resistant stainless steel screws. Surface Mount Carrier recommended for all surface mount installations.

WINTERIZATION

Shut off water and drain down.

WARRANTY

One year warranty. Labor not included.

SHIPPING WT.

Model 350 SM 45 lbs.

Note: When ordering, please specify stainless steel by SS. Always note your color choice and options where applicable. Example: Specify 350 SMSS to order 350 Surface Mount Stainless Steel. Please call MDF to assist you with ordering, quoting and shipping.

MOST DEPENDABLE FOUNTAINS, INC.
(800) 552-6331 • (901) 867-0039 • Fax (901) 867-4008
5705 COMMANDER DR. • ARLINGTON, TN 38002-0587
www.mostdependable.com

