



PLAY TOWER SPECIFICATIONS

PLAY TOWER 1

PEDESTAL	One piece weld construction with MDF standard $\frac{3}{16}$ " wall thickness or optional 304 schedule 10 stainless steel.
VALVE	Valve is metered and can be set to run 15 seconds to 5 minutes.
WATER PATTERN	Play Tower 1 provides a 42" cascading shower effect.
INSTALLATION	Play Tower 1 is designed to be anchored to a concrete slab by means of our 6" template that is set in concrete. Stainless Steel Surface Carrier included.
WINTERIZATION	Shut off water and drain down.
SUPPLY LINE	Maintenance-free reinforced $\frac{1}{2}$ " nylobraid tubing. Customer connection is a $\frac{3}{4}$ " MIP threaded inlet.
FINISH	Oven-baked powder coat. Color choices: green, blue, brown, black, red, yellow, orange, white and chrome. Textured color choices: emerald, sapphire, pyrite, text-black, burgundy, gold vein, copper and sandstone. Stainless steel models are powder coated for added protection and all colors listed are available.
SHIPPING WT.	150 lbs.

PLAY TOWER 2

PEDESTAL	One piece weld construction with MDF standard $\frac{3}{16}$ " wall thickness or optional 304 schedule 10 stainless steel.
VALVE	Valve is metered and can be set to run 15 seconds to 5 minutes.
WATER PATTERN	At 60 PSI, the diameter of the spray is 20". The spray may be throttled down to provide a smaller spray diameter.
INSTALLATION	Play Tower 2 is designed to be anchored to a concrete slab by means of our 8" template that is set in concrete. Stainless Steel Surface Carrier included.
WINTERIZATION	Shut off water and drain down.
SUPPLY LINE	Maintenance-free reinforced $\frac{1}{2}$ " nylobraid tubing. Customer connection is a $\frac{1}{2}$ " MIP threaded inlet.
FINISH	Oven-baked powder coat. Color choices: green, blue, brown, black, red, yellow, orange, white and chrome. Textured color choices: emerald, sapphire, pyrite, text-black, burgundy, gold vein, copper and sandstone. Stainless steel models are powder coated for added protection and all colors listed are available.
SHIPPING WT.	40 lbs.

PLAY TOWER 3

PEDESTAL	One piece weld construction with MDF standard $\frac{3}{16}$ " wall thickness or optional 304 schedule 10 stainless steel.
VALVE	Valve is metered and can be set to run 15 seconds to 5 minutes.
WATER PATTERN	At 60 PSI, the diameter of the spray is 40" x 40" and the water projects 6' from the pedestal to the top of the water circle.
INSTALLATION	Play Tower 3 is designed to be anchored to a concrete slab by means of our 4" template that is set in concrete. Stainless Steel Surface Carrier included.
WINTERIZATION	Shut off water and drain down.
SUPPLY LINE	Maintenance-free reinforced $\frac{1}{2}$ " nylobraid tubing. Customer connection is a $\frac{1}{2}$ " MIP threaded inlet.
FINISH	Oven-baked powder coat. Color choices: green, blue, brown, black, red, yellow, orange, white and chrome. Textured color choices: emerald, sapphire, pyrite, text-black, burgundy, gold vein, copper and sandstone. Stainless steel models are powder coated for added protection and all colors listed are available.
SHIPPING WT.	130 lbs.

MOST DEPENDABLE FOUNTAINS, INC.
(800) 552-6331 • (901) 867-0039 • Fax (901) 867-4008
5705 COMMANDER DR. • ARLINGTON, TN 38002-0587
www.mostdependable.com