



# SAFE-STREAM SERIES DRINKING FOUNTAIN SPECIFICATIONS

## WATER QUALITY (LEAD FREE)

Fountain meets NSF-61 requirements and has a UL approved label with a UL tracking number.

## PEDESTAL

One piece weld construction with MDF standard  $\frac{3}{16}$ " wall thickness **or optional** 304 schedule 10 stainless steel.

## RECEPTOR BOWL

18 gauge electro-polished stainless plated bowl. **Bowl overlaps pedestal by  $\frac{9}{16}$ "**. Prevents build-up of residue in visual drinking area. **Stainless steel Bowl Sand Strainer standard.**

## BUBBLER HEAD

Heavy-duty, stainless steel, self sealing **Safe-Stream Bubbler** (patent pending).

## PUSH BAR

304 stainless steel with **1 $\frac{1}{4}$ " x 2" stainless steel housing**. Low clearance between push bar and housing prevents objects from sticking push bar in the ON position.

## CONTROL VALVE

**Non-cartridge stainless steel O-Ring valve** delivers non-spurt, adjustable steady stream of water. **Washerless.**

## WATER SUPPLY (LEAD FREE)

Maintenance-free reinforced nylobraid tubing and fittings, NSF-61 certified. **This tubing is not plastic.** It is supplied with a  $\frac{1}{2}$ " MIP threaded inlet with a stainless steel strainer. Union fittings at every connection. Supply line stops above grade. **Pedestal units include NSA water filter.**

## FINISH

Oven-baked powder coat. Color choices: green, blue, brown, black, red, yellow, orange, white and chrome. Textured color choices: emerald, sapphire, pyrite, text-black, burgundy, gold vein, copper and sandstone. Stainless Steel fountains are powder coated for added protection and all colors listed are available.

## WASTE

1 $\frac{1}{2}$ " schedule 40 PVC pipe. Waste line stops above grade.

## ACCESS

Working parts accessible through bowl of fountain for easy service.

## INSTALLATION

**Surface Mount** is designed to be anchored on top of an existing surface (concrete, etc.) with anchor bolts through a mounting plate that is welded to the fountain. Surface Mount fountains provide an access door with vandal resistant stainless steel screws. Surface Mount Carrier recommended for all surface mount installations. Access door standard on all pedestal fountains.

## WINTERIZATION

Shut off water and drain down.

## WARRANTY

One year warranty. Labor not included.

## SHIPPING WT.

Model Safe-Stream 10\* SM..... 135 lbs      Model Safe-Stream 50\* WM ..... 45 lbs  
Model Safe-Stream 40\* SM..... 135 lbs      \* Meets ADA regulations

Note: When ordering, always note your color choice and options where applicable. (Options are added at an additional cost to the customer.) Example: Specify Safe-Stream 10 SMSS green to order Safe-Stream 10 Surface Mount Stainless Steel in green. Please call MDF to assist you with ordering, quoting and shipping.

**MOST DEPENDABLE FOUNTAINS, INC.**  
(800) 552-6331 • (901) 867-0039 • Fax (901) 867-4008  
5705 COMMANDER DR. • ARLINGTON, TN 38002-0587  
www.mostdependable.com

